Comparison of Technical Properties Programat®

	EP 3010 G2	EP 5010 G2
Hardware Features		
Widescreen colour display	4.3"	7"
Membrane-sealed keypad & touch display operation	✓	✓
QTK 2 muffle technology with SIC bottom reflector	✓	✓
Electronic press drive with force sensor	✓	✓
Double-valve vacuum technology	~	✓
OSD with status indicator and explanation	✓ ✓	✓
OSD with progress indicator	_	✓
Programat Infrared Technology IRT		✓
Programat WLAN Kit	_	
Software Features		
	✓	✓
New operating concept with modern icons Language options of software	25	25
	300/20	
Individual press and firing programs	300/20	500/20
Individual press and firing programs on USB flash drive		500/-
Preset Ivoclar Vivadent press and firing programs	✓	✓
FPF - Fully automatic press function	<u> </u>	✓
"CDS" Crack Detection System	✓	✓
"TSP" Thermo Shock Protection	<u> </u>	✓
Different operating modes	✓	✓
Predrying program (indiv. time/temp.)	✓	✓
Noise-reduced operation of vacuum pump	✓	✓
Power Saving Technologie	✓	✓
Integrated voltage indicator	✓	✓
Electronic Vacuum Control System (EVCS)	✓	✓
Program bypass in case of power failure	✓	✓
Muffle cleaning program	✓	✓
Dehumidification program	✓	✓
Modern signal tunes	✓	✓
Remote diagnostics via diagnostic file	✓	✓
Integrated test programs (e.g. heating, vacuum, etc.)	✓	✓
Software update via USB flash drive	✓	✓
Display of notes and errors with text	✓	✓
Operation and programming via notebook/PC	✓	✓
Firing protocols for QA via notebook/PC	✓	✓
IoT connectivity	✓	✓
Software update via WLAN	-	✓
Picture Manager via notebook/PC/Programat App		✓
Preset timer function	-	✓
Integrated program copy assistant	-	✓
IR-operated closing process	-	✓
IR-operated predrying		✓
IR-operated recognition of the investment ring size		
IR-operated temperature measurement of the investment ring		 ✓
MP3 and video player	-	✓
Picture viewer		✓
DSA - Digital Shade Assistant	_	✓
Temperature Calibration		
Calibration	Automatically	Automatically
Adjustable calibration interval		✓
Automatic double-range calibration		✓
Design and Ergonomics		
Large cooling tray	✓	✓
Integrated tong holder	✓	✓
Removable furnace head	✓	✓
Integrated cable duct	✓	✓
Swivel keypad unit	-	✓
Connections		
USB	1	3

Ethernet (LAN)	✓	✓
WLAN	_	✓
SD Card Reader	_	✓
Audio connections (in/out)	-	 ✓
Technical Data		
200-240 V / 50-60 Hz	✓	✓
110-120 V / 50-60 Hz	✓	✓
Max. power consumption at 110–120 V (Ampere)	12	12
Max. power consumption at 200 – 240 V (Ampere)	8.5	8.5
Max. heating rate	140 °C/min	140 °C/min
Warranty		
Warranty period*	2 years	3 years

 \checkmark

✓ Standard delivery form

USB host

not available
 * excluding consumables

Date information prepared: 2021-05

ivoclar vivadent:

~